RJS030 ULTRABOOST 1500A LITHIUM JUMP STARTER



The ULTRABOOST 1500A is capable of jump-starting vehicles with up to 6L Petrol and 3L Diesel engines. Suitable for most 12V cars, vans, SUVs and LCVs.

The ULTRABOOST allows users to jump-start completely depleted batteries using the new boost button. The unique ergonomic smart clamp clamp connection is equipped with longer cables to improve accessibility for harder to reach batteries. Ringtelligence technology for safer vehicle maintenance is included in the design of the clamps, offering reverse polarity protection, anti-spike protection and short circuit protection.

The integrated torch illuminates the work area whilst the large LCD screen clearly displays the current battery level. The USB-C port with PD60W fast charge technology allows for fast recharging of the ULTRABOOST unit and high power delivery to recharge devices such as laptops, tablets and phones.

- ULTRABOOST enables users to safely start vehicles with completely depleted batteries
- Powerful delivery with Peak Amps of 1500A and 350A Starting Amps for engines up to 6L Petrol and 3L Diesel
- Ringtelligence keeps users safe with reverse polarity protection and spark-free design
- Suitable for START/STOP batteries
- Unique ergonomic smart clamp battery terminal for secure, safe connection and easy reach cables perfect for harder to reach batteries
- PD60W Technology enables rapid recharging and fast charging of devices such as laptops, tablets and phones
- USB-C to USB-C and USB-A to USB-C cable included
- Clear LCD display and LED torch for use in low light conditions
- Anti-slip base to stop the unit sliding on the engine bay
- Compact and lightweight making it easy to handle and store within the vehicle
- Protective storage case included







Ring Automotive Limited

Gelderd Road, Leeds, LS12 6NA United Kingdom Telephone +44 (0)113 213 2000 . Fax +44 (0)113 231 0266 Email: autosales@ringautomotive.com . www.ringautomotive.com

Specifications

Product Code	RJS030
Lithium Battery Capacity	12,000mAh
Start Current: 200A	350A
Peak Current: 500A	1500A
USB-C (input/output)	PD60W
USB (output)	Quick Charge (5V/9V/12V)
Charging Time	<1.5 Hours
Weight	1.13kg
Dimensions	L201 x W134 x D113mm
Quantity	4 x 1
Barcode	5055175252612



In-built safety features to protect from accident or incorrect use, including: Reverse polarity protection Anti-spike protection Short circuit protection

Authorised Representative: OSRAM GmbH Nonnendammallee 44, 13629 Berlin, Germany Email: automotive-service@osram.com www.osram.com

