


SMARTCHARGE PRO 100A BATTERY CHARGER

For workshop and showroom use




۲



Suitable for

۲



• 12V and 24V compatible ideal for intensive use with fleets of mixed vehicles Including cars, LCV and HGVs, plus in commercial garages and workshops

• Up to 100A continuous charge. Power supply:	
12V default: 13.4V Max. 100A.	
Manual adjustable: 12V to 14.9V Max. 50A	
24V default: 26.8V Max. 80A	
Manual adjustable: 24V to 28.9V Max. 80A	
Rapid recharge in minutes	
Stop/Start compatible	

- Variable charging rates: 12V @ 5/10/30/50/60/100A; 24V @ 5/10/30/50/60/80A For slow or rapid recharge that can get a battery to start in minutes
- 9-Stage charging process for Lead Acid/Gel/AGM/Calcium/EFB batteries
- 7-Stage lithium charging process for Lithium batteries
- Large LCD colour screen
- To see charge status clearly in low light
- Battery and alternator diagnosis To check potential starting problems and cranking ability
- Pre-charge health check for your engine system
- Easy to use menu system Making it intuitive to use removing any hassle when working
- Removable fully insulated high capacity battery clamps Provide enhanced user safety

Manufactured & Imported by: Ring Automotive Limited Gelderd Road, Leeds, LS12 6NA United Kingdom

Telephone +44 (0)113 213 2000 . Fax +44 (0)113 231 0266 Email: autosales@ringautomotive.com . www.ringautomotive.com



Specifications

Product Code	RSCP10024
Voltage Output	12/24V DC
Voltage Input	220-240V AC
Charger Rate	12V@100A; 24V@80A
Battery Type	Lead Acid, Gel, Calcium, EFB, AGM & LiFePO4
Max. Battery Capacity	1000Ah
Min. Battery Capacity	14Ah
Packaging Dimensions	415 x 385 x 117mm
Pack Weight	7.5kg
Case Quantity	2 x 1
Barcode	5055175250809

DESIGNED WITH THE PROFESSIONAL IN MIND

Imported by: OSRAM GmbH

Nonnendammallee 44, 13629 Berlin, Germany Email: automotive-service@osram.com www.osram.com

CAT1654

01/03/2022 11:12

۲