



RTS450 Flat Tyre Sealant

450ml



- **Made to original car makers specification**

- **Particle Gel Sealant technology**

- **450ml Tyre Sealant**

- **Direct replacement**

For the original sealant that came with your vehicle

- **Different to foam sealant**

Can be cleaned easily by rinsing the sealant from the tyre with water to allow the tyre to be repaired

- **Quick repair solution**

Get back on the road in under 10 minutes

- **TPMS safe**

Ring Sealant does not damage TPMS sensors

- **Suitable for use in all weather conditions**

- **Drive for up to 200km / 125 miles**

before professional repair

- **Valve though sealant**

No need to remove the valve core

- **Can repair punctures up to 6mm wide***

- **Compatible with most air compressors (Min 3 bar, Max 8 bar)**

- **No need for Jacks or Tools**

- **Replace every 5 years**

- **Use of environmentally friendly materials**



Specifications

Product Code	RTS450
Quantity	450ml
Max Tyre Size Use	21"
Max. Distance after repair	200km @ 80km/h before repairing the tyre 125 miles @ 50mph before repairing the tyre
Usage	-20°C to +60°C
Sealant weight	0.60Kg
Total Pack weight	0.65Kg
Case quantity	6 x 1
Barcode	5055175245881

*Not suitable to repair tyres that have come off the rim, have sidewall damage, ripped tyres or punctures larger than 6mm

Ring Automotive Limited . Gelderd Road, Leeds, LS12 6NA United Kingdom

Telephone +44 (0)113 213 2000 . Fax +44 (0)113 231 0266

Email autosales@ringautomotive.com . www.ringautomotive.com

[f](#) [t](#) [in](#) [yt](#) /ringautomotive



CAT1405