

RSC1005

ULTRACHARGE 5A SMART BATTERY CHARGER

ULTRACHARGE 5A is part of Ring's most advanced smart charger range to date, engineered for effortless and intelligent battery maintenance. It optimises performance through a 9-stage charging cycle for Lead Acid, AGM and Calcium batteries, and a dedicated safe 7-stage cycle specifically for Lithium.

With built-in battery repair and alternator test functions, ULTRACHARGE helps diagnose faults, restore performance, and extend battery life, making it the ultimate all-in-one charging solution.

Its extra-long cables provide flexibility for easy reach into most engine bays, while automatic maintenance mode prevents overcharging once your battery is fully charged. Durable and dependable, the ULTRACHARGE 5A is IP65 weatherproof, ensuring safe use in all conditions.









Weather proof





- 6V and 12V compatible Charge and maintain the majority of vehicle types including motorcycles, cars, vans and LCVs.
- 2A/5A charge rate selection Efficient charging with charge rate up to 5A.
- Repair mode Helps restore battery health and extending lifespan.
- Alternator tester Diagnose battery charging issues with dedicated
- **Extra-long cables** Easily reach the engine bay in most vehicle types.
- 9-Stage charging process Safely optimises battery health for long
- 7-Stage Lithium charging process Dedicated 7-stage charging mode to charge and maintain modern Lithium batteries.
- Long-term maintenance mode Automatically engages after charging to maintain and optimise battery health.
- IP65 Rating Suitable for use in poor weather conditions.
- STOP/START Compatible Safely recharges batteries fitted to vehicles with stop/start functionality.
- Convenient carry bag Ideal for storage and portability.

Ring Automotive Limited

Gelderd Road, Leeds, LS12 6NA United Kingdom Telephone +44 (0)113 213 2000 . Fax +44 (0)113 231 0266 Email: autosales@ringautomotive.com . www.ringautomotive.com 📝 🗿 in 🔠 /ringautomotive





Specification

Product Code	RSC1005
Voltage Output	6V/12V DC
Voltage Input	220-240V AC
Charger Rate	Up to 5A
Battery Type	Lead Acid, Gel, Calcium, EFB, AGM & Lithium
Max. Battery Capacity	120Ah charging, 160Ah maintenance
Min. Battery Capacity	4Ah
Power Cable Length	1.8m
Battery Cable Length	2.5m
IP Rated	IP65
Product Dimensions	L126 x W84 x H52mm
Case Quantity	4 x 1
Barcode	5055175250120

Authorised Representative: OSRAM GmbH

www.osram.com

Nonnendammallee 44, 13629 Berlin, Germany Email: automotive-service@osram.com