

# **RSC908T 8A SMART BATTERY CHARGER AND MAINTAINER**

### Safe and easy-to-use.

For traditional, Lithium and Stop/Start batteries.







Crocodile clips

nd O ring



START STOP





## **Features**

- 12V and 24V compatible
- Charge multiple vehicle types from cars, vans, LCVs and HGVs
- Up to 2A or 8A charge rate selection
- Efficient Charging wth a max charge rate up to 8A.
- **STOP/START compatible** Will safely recharge STOP/START batteries. .
- 9-Stage charging process Will optimise the battery health for long term use.
- . 7 stage Lithium Charging Process Specifically to optimise the health of lithium batteries.
- Large LCD display screen Clearly shows voltage and charging progress.
- **IP65 Rating** For safe use in rain or snow. •
- **Cold weather charging mode** Protects batteries in cold temperatures.
- Quick connectors Connect quickly with clamps or use the included O-ring terminals to add a permanent connection.
- . Backlit display To help read in low light conditions.
- One button operation for ease-of-use Simple and intuitive to use
- . Safe and Secure Built in short-circuit protection and reverse polarity protection.
- Connect and be sure . Automatically adjusts to long-term maintenance mode when battery is full.

#### **Ring Automotive Limited**

Gelderd Road, Leeds, LS12 6NA United Kingdom Telephone +44 (0)113 213 2000 . Fax +44 (0)113 231 0266 Email: autosales@ringautomotive.com . www.ringautomotive.com 🖸 💿 🔠 /ringautomotive





Battery types

-	
Product Code	RSC908T
Voltage Output	12V/24V DC
Voltage Input	230V AC
Charger rate	12V: Up to 8A 24V Up to 4A
Battery Type	Lead Acid, Gel, Calcium, EFB & AGM, Lithium
Max. Battery Capacity	12V: Up to 150Ah 24V: Up to 70Ah
Min. Battery Capacity	4Ah
Product Dimensions	H182 x W106 x D65mm
Case Quantity	6x1
Barcode	5055175263595

#### Authorised Representative: **OSRAM GmbH**

**Specifications** 

Nonnendammallee 44, 13629 Berlin, Germany Email: automotive-service@osram.com www.osram.com