
# SMARTCHARGE PRO **50A BATTERY CHARGER**




## For workshop and showroom use





#### Suitable for



• 12V and 24V compatible ideal for intensive use with fleets of mixed vehicles Including cars, LCV and HGVs, plus in commercial garages and workshops

#### Up to 50A Continuous charge

POWER SUPPLY: 12V default: 13.4V Max. 50A. Manual adjustable: 12 to 14.9V Max. 50A 24V default: 26.8V Max. 50A. Manual adjustable: 24 to 28.9V Max. 50A

Rapid recharge in minutes

#### Stop/Start compatible

- Variable charging rates 12/24V at 5/10/30/50A For slow or rapid recharge that can get a battery to start in minutes
- 9-Stage charging process for Lead Acid/Gel/AGM/Calcium/EFB batteries
- 7-Stage lithium charging process for Lithium batteries
- Large LCD display screen
- To see charge status clearly in low light
- Battery and alternator diagnosis
- To check potential starting problems and cranking ability
- Pre-charge health check for your engine system
- Easy to use menu system
- Making it intuitive to use removing any hassle when working
- Removable fully insulated high capacity battery clamps Provide enhanced user safety

#### **Ring Automotive Limited**

Gelderd Road, Leeds, LS12 6NA United Kingdom Telephone +44 (0)113 213 2000 . Fax +44 (0)113 231 0266 Email: autosales@ringautomotive.com . www.ringautomotive.com f 오 🗿 🛅 /ringautomotive



#### Specifications

Product Code	RSCP5024
Voltage Output	12/24V DC
Voltage Input	220-240V AC
Charger Rate	50A
Battery Type	Lead Acid, Gel, Calcium, EFB, AGM & LiFePO4
Max. Battery Capacity	500Ah
Min. Battery Capacity	14Ah
Packaging Dimensions	407 x 362 x 117mm
Pack Weight	7kg
Case Quantity	2 x 1
Barcode	5055175249315

# DESIGNED WITH THE PROFESSIONAL IN MIND

### Authorised Representative: **OSRAM GmbH**

Nonnendammallee 44, 13629 Berlin, Germany Email: automotive-service@osram.com www.osram.com