

LED AUTOMOTIVE LIGHTING



WORKLAMPS







ANCILLARY LIGHTING BE SAFE – BE SEEN.

Safety at work is paramount to us all, even more so when your workspace is mobile.

At the kerbside or on work sites, dangerous operating situations may be unavoidable, especially as third parties might also be involved.

Work lighting will help you and your team be seen and be safe.



12/24V 1900 LUMENS 9 LED **SQUARE WORKLAMP**

Dual Voltage

12/24V

Reg 10

27W



RCV9578

12/24V 1500 LUMENS 4 LED **SQUARE WORKLAMP**

Dual Voltage

12/24V

Reg 10

20W



Specifications

•	
Product Code	RCV9577
Function:	Flood Beam Worklamp
Lens:	Clear
Wattage:	27W Raw Wattage
Current Draw:	2.25A @ 12V; 1.13A @ 24V
Light Source:	9 x 3W LED
Light Output:	1900 Lumens
Housing Material:	Aluminium Alloy
Lens Material:	PC
Cable Length:	400mm
Product Dimensions:	100 x 116 x 47mm
Barcode	5055175253152

Product Code	RCV9578
Function:	Flood Beam Worklamp
Lens:	Clear
Wattage:	20W Raw Wattage
Current Draw:	1.7A @ 12V; 0.85A @ 24V
Light Source:	4 x 10W LED
Light Output:	1500 Lumens
Housing Material:	Aluminium Alloy
Lens Material:	PC
Cable Length:	300mm
Product Dimensions:	75.5 x 112 x 47mm
Barcode	5055175253169

WORKLAMPS

RCV9571

ROUND WORKLAMP

Dual Voltage

12/24V

Reg 10

36W

RCV9572

12/24V 1300 LUMENS 18 LED 12/24V 2200 LUMENS 9 LED

ROUND WORKLAMP

Dual Voltage

12/24V

Reg 10

20W





Specifications

•	
Product Code	RCV9571
Function:	Flood Beam Worklamp
Lens:	Clear
Wattage:	36W Raw Wattage
Current Draw:	3A @ 12V; 1.5A @ 24V
Light Source:	18 x 2W LED
Light Output:	1300 Lumens
Housing Material:	Aluminium Alloy
Lens Material:	PC
Cable Length:	300mm
Product Dimensions:	144 x 122 x 40mm
Barcode	5055175253091

Product Code	RCV9572
Function:	Flood Beam Worklamp
Lens:	Clear
Wattage:	20W Raw Wattage
Current Draw:	1.7A @ 12V; 0.85A @ 24V
Light Source:	9 x 3W LED
Light Output:	2200 Lumens
Housing Material:	Aluminium Alloy
Lens Material:	PC
Cable Length:	300mm
Product Dimensions:	Ø113 x 48.5mm
Barcode	5055175253107



RCV9574

12/24V 2000 LUMENS 16 LED 12/24V 1200 LUMENS 9 LED

SQUARE WORKLAMP

Dual Voltage

12/24V





SQUARE WORKLAMP

Dual Voltage

12/24V









Specifications

Product Code	RCV9573	
Function:	Spot/Flood Beam Worklamp	
Lens:	Clear	
Wattage:	40W Raw Wattage	
Current Draw:	3.33A @ 12V; 1.66A @ 24V	
Light Source:	16 x 3W LED	
Light Output:	2000 Lumens	
Housing Material:	Aluminium Alloy	
Lens Material:	PC	
Cable Length:	300mm	
Product Dimensions:	110 x 128 x 57mm	
Barcode	5055175253114	

Product Code	RCV9574
Function:	Spot/Flood Beam Worklamp
Lens:	Clear
Wattage:	27W Raw Wattage
Current Draw:	2.25A @ 12V; 1.13A @ 24V
Light Source:	9 x 3W LED
Light Output:	1200 Lumens
Housing Material:	Aluminium Alloy
Lens Material:	PC
Cable Length:	300mm
Product Dimensions:	109 x 138 x 41mm
Barcode	5055175253121

DRIVING LAMPS

RCV9575

12/24V 700 LUMENS 8 LED OVAL WORKLAMP

Dual Voltage

12/24V Voltage Reg 10

20W

RCV9576

12/24V DRIVING LAMP WITH SIDELIGHT

Dual Voltage

12/24V

Reg 10

Reg 148

Reg 149





Specifications

•	
Product Code	RCV9575
Function:	Flood Beam Worklamp
Lens:	Clear
Wattage:	20W Raw Wattage
Current Draw:	1.7A @ 12V; 0.85 @ 24V
Light Source:	8 x 3W LED
Light Output:	700 Lumens
Housing Material:	Aluminium Alloy
Lens Material:	PC
Cable Length:	300mm
Product Dimensions:	141.5 x 90 x 64.5mm
Barcode	5055175253138

Product Code	RCV9576
Function:	Driving Lamp with Sidelight
Lens:	Clear
Current Draw:	High beam: 1.16 - 1.25A Position light: 0.025A
Light Source:	High beam: 12 x 4W LED Position light: 7 x 0.5W LED
Light Output:	Reg 148 / Reg 149
Housing Material:	PA
Lens Material:	PC
Cable Length:	300mm
Product Dimensions:	244 x 138.5 x 110mm
Barcode	5055175253145

TRAILER LIGHTS



RCV4606

12/24V SLIMLINE **HAMBURGER LAMP**

WITH STOP/TAIL/INDICATOR

Dual Voltage









RCV4607

12/24V HAMBURGER LAMP **WITH BUCKET**

WITH STOP/TAIL/INDICATOR

Dual Voltage











Specifications

Product Code	RCV4606
Function:	Combined lamp with stop/tail/indicator
Lens:	Red/amber
Wattage:	3.2W
Current Draw:	0.3A @ 12V; 0.15A @ 24V
Light Source:	20 x 0.2W SMD LED
Light Output:	Reg 6 / Reg 7
Housing Material:	ABS
Lens Material:	PMMA
Cable Length:	200mm
Product Dimensions:	Ø140 x 25mm
Barcode	5055175253206

Combined lamp with stop/tail/indicator
Red/amber
3.2W
0.3A @ 12V; 0.15A @ 24V
20 x 0.2W SMD LED
Reg 6 / Reg 7
ABS
PMMA
Ø140 x 85.5mm
5055175253213

TRAILER LIGHTS

RCV4608

12/24V LEFT COMBI LAMP

WITH DYNAMIC INDICATOR

Dual Voltage

Reg 3	Reg 6	Reg 7
Reg 10	Reg 23	Reg 38
Approved	Approved	Approved



RCV4609

12/24V RIGHT COMBI LAMP WITH DYNAMIC

WITH DYNAMIC INDICATOR

Dual Voltage

Reg 3	Reg 6	Reg 7
Approved	Approved	Approved
Reg 10	Reg 23	Reg 38
Approved	Approved	Approved



Specifications

Product Code	RCV4608		
Function:	Rear combination lamp - left		
Lens:	Red/amber/clear		
Wattage:	4W		
Current Draw:	0.4A @ 12V; 0.2A @ 24V		
Light Output:	Stop: 2.3W Tail: 0.5W Reverse: 2.3W Sidelight: 2.0W Rear fog: 4.0W		
Housing Material:	PC		
Lens Material:	PMMA		
Cable Length:	500mm		
Product Dimensions:	252 x 133 x 28.5mm		
Barcode	5055175253206		

Product Code	RCV4609
Function:	Rear combination lamp - right
Lens:	Red/amber/clear
Wattage:	4W
Current Draw:	0.4A @ 12V; 0.2A @ 24V
Light Output:	Stop: 2.3W Tail: 0.5W Reverse: 2.3W Sidelight: 2.0W Rear fog: 4.0W
Housing Material:	PC
Lens Material:	PMMA
Cable Length:	500mm
Product Dimensions:	252 x 133 x 28.5mm
Barcode	5055175253237
	•



12/24V LEFT

FLEXIBLE STALK LAMP

Dual Voltage

12/24V Voltage

Reg 7 Approved

Reg 10

Reg 91 Approved RCV4026

12/24V RIGHT FLEXIBLE STALK LAMP

Dual Voltage

12/24V Voltage

Reg 7 Approved

Reg 10

Reg 91 Approved RCV4027

12/24V MARKER FLEXIBLE STALK LAMP

Reg 7

Reg 10 Approved

Reg 91







Specifications

	Product Code	RCV4025	
	Function:	Side marker - left	
	Lens:	Red/amber/clear	
	Wattage:	1.8W	
	Current Draw:	0.15A @ 12V; 0.08A @ 24V	
	Housing Material:	EPDM	
	Lens Material:	PMMA	
	Cable Length:	200mm	
	Product Dimensions:	176 x 110 x 85mm	
	Barcode	5055175253275	

Specifications

Opecinications -			
Product Code	RCV4026		
Function:	Side marker - right		
Lens:	Red/amber/clear		
Wattage:	1.8W		
Current Draw:	0.15A @ 12V; 0.08A @ 24V		
Housing Material:	EPDM		
Lens Material:	PMMA		
Cable Length:	200mm		
Product Dimensions:	176 x 110 x 85mm		
Barcode	5055175253282		

Product Code	RCV4027	
Function:	Side marker - universal	
Lens:	Red/amber/clear	
Wattage:	1.8W	
Current Draw:	0.15A @ 12V; 0.08A @ 24V	
Housing Material:	EPDM	
Lens Material:	PMMA	
Cable Length:	200mm	
Product Dimensions:	100 x 50 x 85mm	
Barcode	5055175253305	

LIGHT BARS

RCV9761

AMBER MINI LIGHT BAR

Dual Voltage















Specifications

- p	
Product Code	RCV9761
Function:	Amber light bar
Lens:	Clear
Wattage:	20W
Current Draw:	1.7A @ 12V, 0.85A @ 24V
Light Source:	40 x 1W LED
Housing Material:	ABS
Lens Material:	PC
Cable Length:	500mm
Product Dimensions:	58 x 343 x 197mm
Barcode	5055175246451

RCV9762

0.7M AMBER MINI LIGHT BAR

Dual Voltage



















Product Code	RCV9762
Function:	Amber light bar
Lens:	Clear
Wattage:	80W
Current Draw:	6.7A
Light Source:	80 x 1W LED
Housing Material:	ABS
Lens Material:	PC
Cable Length:	500mm
Product Dimensions:	45 x 717 x 265mm
Barcode	5055175247809



0.9M AMBER MINI LIGHT BAR

Dual Voltage

















RCV9764

1.2M AMBER **MINI LIGHT BAR**

Dual Voltage























Specifications

Product Code	RCV9763	
Function:	Amber light bar	
Lens:	Clear	
Wattage:	96W	
Current Draw:	8A	
Light Source:	96 x 1W LED	
Housing Material:	ABS	
Lens Material:	PC	
Cable Length:	500mm	
Product Dimensions:	45 x 877 x 265mm	
Barcode	5055175247816	

Product Code	RCV9764
Function:	Amber light bar
Lens:	Clear
Wattage:	128W
Current Draw:	10.7A
Light Source:	128 x 1W LED
Housing Material:	ABS
Lens Material:	PC
Cable Length:	500mm
Product Dimensions:	45 x 1196 x 265mm
Barcode	5055175247823

STROBES

RCV2218

12/24V LED

AMBER STROBE

Dual Voltage









12/24V 3 LED

AMBER STROBE

Dual Voltage











AMI	BER FLASH PATTERN	S	
1	Single Flash (ECE): 480 ms	6	Quad Flash: 800 ms
2 Single Flash (SAE): 800 ms		7	Single (L&R): 480 ms
3	Double Flash: 480 ms	8	Single (L&R): 800 ms
4	Double Flash: 800 ms	9	Strobe: 60 ms
5	Quad Flash: 480 ms		

AMBER FLASH PATTERNS			
1	Single Flash (ECE): 480 ms	6	Triple Flash: 800 ms
2	Single Flash (SAE): 800 ms	7	Quad Flash: 480 ms
3	Double Flash: 480 ms	8	Quad Flash: 800 ms
4	Double Flash: 800 ms	9	Strobe: 100 ms
5	Triple Flash: 480 ms	10	Cruise

Specifications

•	
Product Code	RCV2218
Function:	Amber Strobe
Lens:	Clear
Wattage:	9.5W
Current Draw:	0.8A@12V; 0.4A@24V
Light Source:	LED
Housing Material:	Plastic
Lens Material:	PC
Cable Length:	300mm
Product Dimensions:	130 x 34 x 16mm
Barcode	5055175253299

Product Code	RCV2219
Function:	Amber Strobe
Lens:	Clear
Wattage:	6.3W
Current Draw:	0.5A@12V; 0.25A@24V
Light Source:	LED
Housing Material:	ADC12
Lens Material:	PC
Cable Length:	300mm
Product Dimensions:	80 x 29 x 10mm
Barcode	5055175253312

MARKER LIGHTS



RCV4006

12/24V 2W

REAR MARKER RED

Dual Voltage







RCV4007

12/24V 1.4W

SIDE MARKER AMBER

Dual Voltage



Reg 10 Approved

Reg 91





Specifications

Product Code	RCV4006
Function:	Rear Marker
Lens:	Red
Cable Length:	300mm
Product Dimensions:	127 x 38 x 11mm
Barcode	5055175253299

Product Code	RCV4007
Function:	Side Marker
Lens:	Amber
Cable Length:	300mm
Product Dimensions:	127 x 38 x 11mm
Barcode	5055175253077

MARKER LIGHTS

RCV4008

12/24V 1.2W

FRONT MARKER WHITE

Dual Voltage







RCV4009

12/24V 0.4W

SIDE MARKER AMBER

Dual Voltage











Specifications

Product Code	RCV4008
Function:	Front Marker
Lens:	Clear
Cable Length:	300mm
Product Dimensions:	127 x 38 x 11mm
Barcode	5055175253084

Product Code	RCV4009
Function:	Side Marker
Lens:	Amber
Cable Length:	200mm
Product Dimensions:	126 x 38 x 10mm
Barcode	5055175253244



12/24V 1W

REAR MARKER RED

Dual Voltage









RCV4024

12/24V 1W

FRONT MARKER WHITE

Dual Voltage









Specifications

Product Code	RCV4023
Function:	Rear Marker
Lens:	Red
Cable Length:	250mm
Product Dimensions:	110 x 45 x 21mm
Barcode	5055175253251

Product Code	RCV4024
Function:	Front Marker
Lens:	Clear
Cable Length:	250mm
Product Dimensions:	110 x 45 x 21mm
Barcode	5055175253268



Ring Automotive Limited . Gelderd Road, Leeds, LS12 6NA United Kingdom Telephone +44 (0)113 213 2000 Fax +44 (0)113 231 0266

 $Email\ autosales@ringautomotive.com\ .\ www.ringautomotive.com$

📝 🗿 in 🔠 /ringautomotive

In line with our policy of continuous product development, Ring Automotive Limited, reserve the right to alter specification without notice. Whilst every care has been taken in compiling the information in this catalogue, Ring Automotive Limited cannot accept legal liability for any errors or omissions. Manufacturers' names and part numbers are for reference only. Illustrations are intended only to be representative of the parts offered, sizes quoted are nominal. © Copyright 2024 Ring Automotive Limited.